



BOARD OF HISTORIC PRESERVATION

Promoting the use and conservation of historic properties for the education, inspiration, pleasure and enrichment of the citizens of Sioux Falls

4:00 p.m. Wednesday, October 14, 2015 Commission Room, City Hall REGULAR MEETING AGENDA

Facilitator: Dixie Hieb, Chair

Call to order

1. Approval of the August 12 and September 9, 2015 Meeting Minutes
(Board action required) Chair
2. Public input on non-agenda items Chair
3. New business:
 - a. 1205 3rd Ave. Raze Garage
All Saints Historic District
(Board Action Required) Kelly Jo Castle, Homeowner (relative)
 - b. Longfellow Elementary/Dakotabilities
Façade Easement
(Information Only) Adam Roach, Community Development
 - c. Pendar Lane Historic Nomination - Update Diane
 - d. Neighborhood & Preservation Summit
Nov. 13 & 14 Bob Yapp Guest Speaker Diane
 - e. Next month's meeting falls on a holiday
Reschedule for Friday Nov. 13 before Bob Yapp Seminar
at 2:00 at the Downtown Library? Diane
4. Other Business:
 - a. New Items?

Adjournment

*The next meeting of the Board of Historic Preservation will be on November 13, 2015 at 2:00pm
Downtown Library, 200 N. Dakota Ave.*

24:52:07:04. Standards for new construction and additions in historic districts. New construction or additions within a historic district must comply with **The Secretary of the Interior's Standards for the Treatment of Historic Properties** as incorporated by reference in § 24:52:07:02. In addition the following standards apply:

(1) Compatibility of design. Massing, size, and scale of new construction must be compatible with surrounding historic buildings. Overall architectural features of new construction must be of contemporary design which does not directly mimic historic buildings. Architectural elements such as windows, doors, and cornices must be similar in rhythm, pattern, and scale to comparable elements in adjacent historic buildings. The overall visual appearance of new construction may not dominate or be distracting to the surrounding historic landscape;

(2) Height. The height of new buildings or additions to existing buildings may not exceed a standard variance of ten percent of the average height of historic buildings on both sides of the street where proposed new construction is to be located;

(3) Width. The width of new buildings or additions to existing buildings must be similar to adjacent historic buildings;

(4) Proportion. The relationship between the height and width of new buildings or additions to existing buildings must be similar in proportion to existing historic buildings. The proportion of openings in the facades of new construction or additions must be compatible with similar openings in adjacent historic buildings;

(5) Rhythm and scale. The rhythm, placement, and scale of openings, prominent vertical and horizontal members, and separation of buildings which are present in adjacent historic buildings must be incorporated into the design of new buildings or additions to existing buildings;

(6) Materials. Materials which make up new buildings or additions to existing buildings must complement materials present in nearby historic properties. New materials must be of similar color, texture, reflective qualities, and scale as historical materials present in the historic district;

(7) Color. The colors of materials, trim, ornament, and details used in new construction must be similar to those colors on existing historic buildings or must match colors used in previous historical periods for identical features within the historic district;

(8) Details and ornament. The details and ornament on new buildings or additions to existing buildings must be of contemporary design that is complementary to those features of similar physical or decorative function on adjacent historic buildings;

(9) Roof shape and skyline. The roof shape and skyline of new construction must be similar to that of existing historic buildings;

(10) Setting. The relationship of new buildings or additions to existing buildings must maintain the traditional placement of historic buildings in relation to streets, sidewalks, natural topography, and lot lines; and

(11) Landscaping and ground cover. Retaining walls, fences, plants, and other landscaping elements that are part of new construction may not introduce elements which are out of character with the setting of the historic district.

Source: 16 SDR 239, effective July 9, 1990; 21 SDR 50, effective September 21, 1994; 24 SDR 73, effective December 4, 1997; 28 SDR 182, effective July 10, 2002.

General Authority: SDCL 1-19A-5, 1-19A-11, 1-19A-29.

Law Implemented: SDCL 1-19A-5, 1-19A-11.1.

Secretary of the Interior's Standards for Rehabilitation

The Standards for Rehabilitation, a section of the Secretary's Standards for Historic Preservation Projects, address the most prevalent preservation treatment today, rehabilitation. Rehabilitation is defined as the process of returning a property to state of utility, through repair or alteration which makes possible an efficient contemporary use while preserving those portions and features of the property which are significant to its historic, architectural and cultural values.

The Standards that follow were originally published in 1977 and revised in 1990 as part of the Department of the Interior regulations (36 CFR Part 67, Historic Preservation Certifications). They pertain to historic buildings of all materials, construction types, sizes, and occupancy and encompass the exterior and the interior of historic buildings. The Standards also encompass related landscape features and the building's site and environment as well as attached, adjacent or related new construction.

The Standards are to be applied to specific rehabilitation projects in a reasonable manner, taking into consideration economic and technical feasibility.

- (1) A property shall be used for its historic purpose or be placed in a new use that requires minimal change to the defining characteristics of the building and its site and environment.
- (2) The historic character of a property shall be retained and preserved. The removal of historic materials or alteration of features and spaces that characterize a property shall be avoided.
- (3) Each property shall be recognized as a physical record of its time, place and use. Changes that create a false sense of historic development, such as adding conjectural features or architectural elements from other buildings, shall not be undertaken.
- (4) Most properties change over time; those changes that have acquired historic significance in their own right shall be retained and preserved.
- (5) Distinctive features, finishes, and construction techniques or examples of craftsmanship that characterize a property shall be preserved.
- (6) Deteriorated historic features shall be repaired rather than replaced. Where the severity of deterioration requires replacement of a distinctive feature, the new feature shall match the old in design, color, texture, and other visual qualities and, where possible, materials. Replacement of missing features shall be substantiated by documentary, physical, or pictorial evidence.
- (7) Chemical or physical treatments, such as sandblasting, that cause damage to historic materials shall not be used. The surface cleaning of structures, if appropriate, shall be undertaken using the gentlest means possible.
- (8) Significant archeological resources affected by a project shall be protected and preserved. If such resources must be disturbed, mitigation measures shall be undertaken.
- (9) New additions, exterior alterations, or related new construction shall not destroy historic materials that characterize the property. The new work shall be differentiated from the old and shall be compatible with the massing, size, scale, and architectural features to protect the historic integrity of the property and its environment.
- (10) New additions and adjacent or related new construction shall be undertaken in such a manner that if removed in the future, the essential form and integrity of the historic property and its environment would be unimpaired.